

## SINGLE STAGE

COMPRESSOR	MOTOR		FAD@8 KG/CM <sup>2</sup>	FAD@10 KG/CM <sup>2</sup>	SOUND LEVEL	COMPRESSOR	DIMENSION	WEIGHT
MODEL	KW	HP	CFM	CFM	dB	RPM	L x W x H (mm)	KG
RR 7.5	5.5	7.5	26	24	68 ± 5	2900	900 x 650 x 920	215
RR 10	7.5	10	40	35	68 ± 5	2900	900 x 650 x 920	215
RR 15	11	15	64	55	68 ± 5	2900	1080 x 700 x 1090	335
RR 20	15	20	85	77	70 ± 5	2900	1080 x 700 x 1090	335
RR 25	18.5	25	110	100	71 ± 5	2900	1300 x 855 x 1150	465
RR 30	22	30	135	114	72 ± 5	2900	1320 x 880 x 1070	468
RR 40	30	40	185	172	72 ± 5	2900	1500 x 1000 x 1330	620
RR 50	37	50	232	215	73 ± 5	2900	1500 x 1000 x 1330	630
RR 60	45	60	275	254	74 ± 5	2900	1500 x 1000 x 1380	825
RR 75	55	75	356	321	75 ± 5	2900	2045 x 1250 x 1705	1250
RR 100	75	100	490	450	76 ± 5	2900	2045 x 1250 x 1705	1450
RR 120	90	120	554	543	76 ± 5	2900	2340 x 1480 x 1820	1820
RR 150	110	150	-	670	76 ± 5	2900	2568 x 1620 x 1985	1970
RR 180	132	180	-	773	76 ± 5	2900	2568 x 1620 x 1985	2400
RR 215	160	215	-	830	77 ± 5	2900	2720 x 1750 x 2125	2600

## SINGLE STAGE

COMPRESSOR	MOTOR		WORKING PRESSURE	FREE AIR DELIVERY	SOUND LEVEL	DIMENSION	WEIGHT
MODEL	KW	HP	KG	CFM	dB	L x W x H (mm)	KG
RR - 15 +	11	15	7-8-10	70-64-55	70 ± 5	910 X 760 X 1090	400
RR - 20 +	15	20	7-8-10	95-89-77	70 ± 5	910 X 760 X 1090	400
RR - 25 +	18.5	25	7-8-10	120-112-100	72 ± 5	1240 X 760 X 1300	550
RR - 30 +	22	30	7-8-10	152-137-117	72 ± 5	1240 X 760 X 1300	550
RR - 40 +	30	40	7-8-10	210-192-172	73 ± 5	1450 X 890 X 1470	750
RR - 50 +	37	50	7-8-10	257-235-215	73 ± 5	1450 X 890 X 1470	800
RR - 60 +	45	60	7-8-10	310-288-254	74 ± 5	1450 X 890 X 1470	850
RR - 75 +	55	75	7-8-10	380-358-321	75 ± 5	1850 X 1060 X 1700	1150
RR - 100 +	75	100	7-8-10	520-490-450	75 ± 5	2000 X 1470 X 1770	1400
RR - 120 +	90	120	7-8-10	635-595-543	75 ± 5	2000 X 1470 X 1770	1900
RR - 150 +	110	150	7-8-10	788-761-659	76 ± 5	2330 X 1500 X 1850	2400
RR - 180 +	132	180	7-8-10	950-905-808	76 ± 5	2330 X 1550 X 1900	2500
RR - 215 +	160	215	7-8-10	1144-1092-988	77 ± 5	2510 X 1650 X 1980	3200
RR - 250 +	185	250	7-8-10	1280-1195-1042	79 ± 5	2790 X 1770 X 2150	3700

## TWO STAGE

COMPRESSOR	MOTOR		WORKING PRESSURE	FREE AIR DELIVERY	SOUND LEVEL	DIMENSION	WEIGHT
MODEL	KW	HP	KG	CFM	dB	L x W x H (mm)	KG
RR - 50 - II	37	50	6-8-10	319-295-262	73 ± 2	1450 X 890 X 1470	970
RR - 60 - II	45	60	6-8-10	395-352-305	74 ± 2	2000 X 1190 X 1650	1390
RR - 75 - II	55	75	6-8-10	490-420-373	75 ± 2	2000 X 1190 X 1650	1900
RR - 100 - II	75	100	6-8-10	653-575-519	75 ± 2	2000 X 1190 X 1650	2000
RR - 120 - II	90	120	6-8-10	784-705-620	76 ± 2	2000 X 1190 X 1650	3000
RR - 150 - II	110	150	6-8-10	950-860-770	76 ± 2	2850 X 1800 X 1900	3150